

Knowledge Base

Information



Abaqus/CAE plug-in to plot contour integrals for conventional and XFEM crack analyses

Portfolio / Domain: SIMULIA Abaqus Unified FEA / SIMULIA Abaqus Unified FEA
Product: SIMULIA Abaqus/CAE

QA Article: QA00000020004e
Applicable Level: 6.10 and higher
Last Update Date: 09.09.2020
Rating: 5.0
Views: 907

QUESTION

I have contour integral history output data. How do I plot the data against node labels and/or distance along the crack front?

ANSWER

(The following applies to Abaqus 6.10 and higher)

An Abaqus/CAE plug-in for this purpose is attached below. It allows you to plot contour integral history output data against:

1. Node labels of conventional crack fronts
2. Node labels of XFEM crack fronts, or
3. Distance along the crack front.
4. Crack front position

For the third option the plug-in computes the straight line distance from the start node as a fixed location to the current node. Whereas for the fourth option, the plug-in approximates the actual length from the start node of the crack front to the current node on the crack front by taking the incremental straight line distance from the current point to the previous point in the crack front node sequence and adding to the accumulated distance from all the prior incremental distances starting at 0.0 at the first node in the sequence.

The plug-in also creates a comma-separated (.csv) file with coordinates of the crack front nodes.

Installation

To install the plug-in, save the attached archive file to one of the following directories:

abaqus_dir\abaqus_plugins where *abaqus_dir* is the Abaqus parent directory

home_dir\abaqus_plugins where *home_dir* is your home directory

current_dir\abaqus_plugins where *current_dir* is the current directory

Note that if the abaqus_plugins directory does not exist in the desired path, it must be created. The *plugin_dir* directory can also be used, where *plugin_dir* is a directory specified in the abaqus_v6.env file by the environment variable **plugin_central_dir**. You can store plug-ins in a central location that can be accessed by all users at your site if the directory to which **plugin_central_dir** refers is mounted on a file system that all users can access. For example,


plugin_central_dir = r\\fileServer\sharedDirectory'

On Windows platforms, right click on the archive files and select **WinZip** → **Extract to here**. On Linux platforms, type **unzip ContourIntegral.zip** at the command prompt. A folder named abq_ContourIntegral and a file named contourIntegral_plugin.py will be extracted.

Note that the plug-in will not function properly if this procedure is not followed.

Usage

In Abaqus/Viewer or the Visualization module of Abaqus/CAE select **Plug-ins** → **Tools** → **Plot Contour Integrals...** to receive the following dialog:





The contour integral history outputs containing crack information will be listed under **Data Extraction**.

Select **Distance** or **Node ID/XFEM crack front ID** for the plot's x-axis values. Depending upon the selected crack name, the respective contour integral parameters and the number of contours will be displayed in the **Y Values** lists. You can select multiple parameters and contours. After the selections, click **Plot** to plot the parameter history data for the current frame of the current step. A check button at the bottom the plug-in dialog provides an option to plot an

average contour integral parameter value for the selected contours. The average plot will be displayed only when the check button is checked and more than one contour is selected in the plug-in dialog. A .csv file will be written to the working directory, which will have the coordinates of the crack front nodes. The name of the file will be Coordinates_.csv.

Each parameter will be plotted on a separate viewport along with the specified contours. For better visualization you may tile the viewports horizontally or vertically. The sample plots for J are shown in the images below.



Limitations

1. For conventional cracks the plug-in is supported **only** when the NORMAL parameter is included with *CONTOUR INTEGRAL keyword in the input file.
2. The use of '_' (underscore) in the crack name string is not supported.
3. For ODBs with a large number of history variables, cracks, contour integrals and contours, the plug-in performance may be affected while populating the plug-in dialog box and plotting the data.
4. The plug-in does not support models involving independent instances in Abaqus/CAE.

Related Links

The XY to Excel plug-in, available in AnswerExporting X-Y data objects output to MS Excel, can be used to export the XY Data to MS Excel.

Revision History

19 Sept 2011	Release of Version 1.1-1
26 Sept 2011	Release of Version 1.1-2 (A bug fixed.)

03 March 2012	Release of Version 1.1-3 (A bug related history ouput string parsing is fixed.)
22 Nov 2013	Release of Version 1.1-4(A bug related to the number of contours > 9)
19 Aug 2015	Release of Version 1.2. Added a new option to use crack front position as X axis for plotting.
11 Nov 2016	Release of Version 1.3. Fixed a bug in determining the ODB version in Abaqus 2016 release.
09 Dec 2019	Fixed a bug when requesting more than 9 contours

Disclaimer

The attachments to this article are subject to certain usage conditions. Please [click here](#) for details.

KEYWORDS **plug-in, plugin, contour, integral, history, output, data, node, labels, id, crack, tip, xfem**

ATTACHMENT

answer_4239_fig2_distance.png

answer_4239_fig3_labels.png

answer_4239_fig1_dialog.png

ContourIntegral.zip

SUBSCRIBE TO CHANGES

☐

RATING

On a scale of 1-5, how would you rate the technical content of the article?
Please rate this article...

LET US KNOW IF THIS ARTICLE NEEDS TO BE ENHANCED

- UNCLEAR
- MISSING INFO
- DUPLICATE
- OUT OF DATE
- ERROR DETECTED

MY FAVORITE CONTENT